





Futuristic Innovations

A new paradigm in LPG Sales -

Explosion proof, Light Weight Cylinders

Presentation by:-







D. Chakraverty

Chief Manager- LPG BD & TU HPCL , Mumbai



Current LPG Marketing Scenario





- ☐ Public sector oil companies (HPCL, BPCL, and IOCL) are marketing LPG in steel cylinders.
- ☐ LPG for Domestic Use is marketed in 'Signal Red' coloured Cylinders.
- ☐ LPG for Commercial use is marketed in 'Oxford Blue' colour cylinders.
- LPG steel cylinders are manufactured and tested as per IS 3196.







Composite Cylinders






Layer 1: The blow molded liner (HDPE) is the seamless inner gas tight layer.

The boss is made of injection molded HDPE with a steel insert.

Layer 2: The composite load carrying material is filament wound fiberglass and epoxy resin which has a tremendous capacity to withstand pressure.

Layer 3: The distinctively designed, injection molded outer casing protects the pressure vessel and valve & makes it convenient for handling.



Worldwide composite cyls used in households, auto-LPG, marine applications & medical requirements.







ADVANTAGES OVER STEEL CYLINDERS

















Composite cylinders

- Light weight,
- Easy to handle.

Steel cylinders

- Heavy









v/s



100% Safe

Steel cylinders

Prone to Explosion

Composite cylinders

Explosion Proof.













Steel cylinders –

Nation's loss due to scrap/corroded metal cylinders

Composite cylinders –

- Non Corrosive- both inside & outside.
- No stain/mark on Floor









V/S



Steel cylinders -

Opaque - Gas level not visible.

Composite cylinders -

Translucent - Gas level visible.









v/s





Steel cylinders – Aesthetically - non appealing.

Composite cylinders –
Aesthetically appealing –
different designs, vibrant
colors.



Journey towards Launch





Market Launch

Statutory Approvals

Bottling facilities

Manufacturing & Testing

Standards



Design, Manufacturing & Testing





Designed, mfd. and tested as per:


- 1. International Standard: ISO 11119 Part 3
- 2. <u>European Standard</u>: EN 12245/ EN 14427
- 3. <u>Indian Standard</u>: Draft standard under wide circulation.




Manufacturing Process











Blow Molding

Boss Welding

Filament Winding







Composite Cylinder



Testing Process







Hydro Test




Leak Test



Ambient Cycle Test



Burst Test



Torque Test







FACILITIES UPGRADATION / INFRASTRUCTURE MODIFICATION

<u>at</u>

LPG Bottling Plants



Facilities / Infrastructure Modification





Purging of Composite cylinders






Facilities / Infrastructure Modification





PRE- FILLING WATER SPRINKLER:

Composite cylinders likely to generate and store static electricity.







acilities / Infrastructure Modification





FILLING:

Semi-automatic electronic filling scale with auto cut off facility is used for filling the composite cylinder.






Facilities / Infrastructure Modification





Q & Q CHECKS:

- CVT to check Valve Leak & "O" Ring Leak.
- ☐ Electronic Check Scale for weight checking of filled cylinders.
- ☐ Metal Boss / Body leak tested in TB.





Coultres / Infrastructure Modification





VALVE CHANGING:

☐ Valve changing done by using a special spanner & torque wrench arrangement.





Landling of Composite Cylinders





- ☐ For convenient and safe handling of composite cylinders, especially designed delivery cages will be used.
- Delivery cages will prevent scratching, scraping, rolling, dropping, dragging, knocking, throwing, etc. of composite cylinders, during any stage of handling.





Dransportation of Composite Cyls.





- ☐ Cylinders will be transported along with their delivery cages through packed trucks/ pick-up vans, in vertically upright & capped position only. Cylinders should be handled either by forklift or trolleys.
- ☐ These composite cylinders will be stored in the existing licensed LPG go downs, by stacking them separately from steel cylinders.







Statutory Approvals





- ☐ In-principle go-ahead from MOP&NG.
- ☐ In-principle approval from PESO, Nagpur.
- ☐ Procurement by HPCL, on behalf of PSU oil industry.
- ☐ Filling permission from PESO, Nagpur.
- ☐ Formulation of BIS Standards



Way Forward







- •Pilot being conducted at Ahmedabad, Pune & Mumbai
- •SKUs being introduced : 2kg, 5kg, 7kg, 10kg & 15kg
- •Further course of action to be decided basis the feedback/experience and further details on following points:
- i. Bottling experience and scalability options.
- ii. Market evaluation, basis acceptability by the consumers.







THANK YOU

Have a nice evening ©

